

GUARDIAN ACRYLIC (INTERIOR / EXTERIOR)

1. PRODUCT BENEFITS:

- 1.1 High opacity, top quality emulsion paint.
- 1.2 Provide excellent exterior durability.
- 1.3 Outstanding range of colours.
- 1.4 Dries to a smooth matt finish with excellent washability.
- 1.5 Easy application with brush or roller.
- 1.6 Quick drying – excellent recoating properties.
- 1.7 Low odour.

2. USES:

- 2.1 A high-grade matt washable wall and ceiling finish for interior / exterior use.
- 2.2 Suitable for direct application to new plaster, concrete, brickwork, and various types of composition boarding.
- 2.3 May also be applied to metal and wooden surfaces provided these surfaces have been primed with appropriate primer.

3. GENERAL DATA:

TYPE	Acrylic- PVA
DRYING TIME AT 25°C	Surface dry: 1/2 –1 hrs → Hard dry 3 –4 hrs
RECOATING TIME	4 HRS
VISCOSITY	100 – 110 Krebs units
SPECIFIC GRAVITY	1,49 – 1,51
SOLIDS BY VOLUME	30 – 40% (depending on colour)
SOLIDS BY MASS	50 – 60% (depending on colour)
SPREADING RATE	Approx. 6- 10 m/1 (depending on surface porosity)
GLOSS	Matt

4. COLOUR RANGE:

- 4.1 Ready mixed colours plus Black and White.

5. APPLICATION:

- 5.1 Ready to use with brush, roller or airless spray. For conventional spray, thin with clean water or PVA sealer.
- 5.2 Not normally thinned but if necessary use water or PVA SEALER. Do not exceed ½ litre/per 5 litre paint. Thinning will reduce opacity.
- 5.3 Clean up –water.

6. SURFACE PREPARATION:

- 6.1 Surfaces must be clean and dry before painting. If used as a self finish on ceiling, all bare metal areas, e.g. nail heads must be primed with an appropriate primer. PRODUCT USE: Interior, exterior PVA has been specially formulated for use as a low cost, high opacity, interior product with a matt finish which can be used on exterior surfaces. Suitable for application to new plaster, concrete, brickwork and composition boarding.

7. PRECAUTION:

- 7.1 Do not apply direct to bare metal surfaces.
- 7.2 Do not paint during wet or cold weather (below 8 °C).

