

SUPER SATIN (GLO) SHEEN

1. PRODUCT BENEFITS:

- 1.1 Top quality scrubbable emulsion paint with a silky appearance for interior decoration.
- 1.2 Easy to apply with brush or roller.
- 1.3 Quick drying – 2 coats can be applied in one day.
- 1.4 Low odour – no paint smell.
- 1.5 Brushes and rollers wash with water.
- 1.6 Non yellowing
- 1.7 Excellent stain removal properties.

2. USES:

- 2.1 Suitable for direct application to new plaster, cement – asbestos lining boards, ceiling boards.
- 2.2 Also suitable for application to metal and wooden surfaces, provided these surfaces are suitable primed before the application of this material.
- 2.3 Useful alternate to ALKYD EGGSHELL ENAMEL, where a low odour quick drying finish is required.

3. GENERAL DATA:

TYPE	PVA
DRYING TIME AT 25°C	Surface dry: ½-1 hr → Hard dry 3-4 hrs
RECOATING TIME	4 hrs
VISCOSITY	75 - 85 kreb units
SPECIFIC GRAVITY	1,35 – 1,38
SOLIDS BY MASS	53 - 54%
SOLIDS BY VOLUME	35 – 37%
SPREADING RATE	Approx. 14,0 m ² /1lt (depending on surface porosity)
GLOSS	Eggshell low sheen (70 – 85/85` head)

4. COLOUR RANGE:

Brilliant White.

5. APPLICATION:

- 5.1 Ready for use with brush, roller, or airless spray for conventional spray thin with clean water. Use a short nap roller for roller application.
- 5.2 Thinning : Not normally thinned but if necessary use water. Thinning will reduce opacity.
- 5.3 Clean – up : Water.

6. SURFACE PREPARATION:

All surfaces must be clean and dry before painting. Previously painted surfaces must be in sound condition. Loose flaking paint and efflorescence must be completely removed and any bare metal areas e.g.: nail heads, spot primed with an appropriate primer. Old enamel or oil paint surfaces must be well sanded. Chalked PVA or distemper surfaces must be well brushed and primed with PLASTER PRIMER. For new work or change in colour, apply two coats. Apply one coat for general maintenance.

7. PRECAUTIONS:

Do not apply to bare un-primed metal surfaces. Not suitable for application to surfaces which exceed 120°C. Essentially a wall coating

8. FLASH POINTS:

Non flammable.