

# CONTRACTORS/FILLERCOAT

## 1. PRODUCT BENEFITS:

- 1.1 High solids Acrylic fillercoat.
- 1.2 Excellent filling properties.
- 1.3 Easy application with a brush or a roller.
- 1.4 Quick-drying – good recoating properties.

## 2. USES:

- 2.1 Essentially a fillercoat /primer for wood floated cement plaster where filling is required prior to top-coating with various latex type finishing coats e.g. PVA Acrylic, etc.
- 2.2 May also be used as a low self-finish for interior use on ceiling boards.

## 3. GENERAL DATA:

TYPE	Acrylic PVA	
DRYING TIME AT 25°C	Surface dry: ½-1 hr	→ Hard dry 3-4 hrs
RECOATING TIME	4 hrs	
VISCOSITY	150 - 225 kreb units	
SPECIFIC GRAVITY	1.5	
SOLIDS BY MASS	68 - 70%	
SOLIDS BY VOLUME	47 - 49%	
SPREADING RATE	Approx. 6 m <sup>2</sup> /1lt (depending on surface porosity)	
GLOSS	Matt	

## 4. COLOUR RANGE:

White.

## 5. APPLICATION:

- 5.1 Ready for use with brush or roller. For airless and conventional spray, thin with clean water.
- 5.2 Thinning: Not normally thinned but if necessary use water. Do not exceed ½/5 litres paint. Thinning will reduce opacity and filling properties.
- 5.3 Clean – up: Water.

## 6. SURFACE PREPARATION:

Surface must be clean and dry before painting. If this product is used as a self finish on ceilings, all bare metal areas e.g. nails heads must be primed with an appropriate primer. This product is not normally used on previously painted surfaces. FILLING: For rough concrete, apply one or two coats depending on the degree of filling required. Apply two coats when used as a self-finish on ceiling.

## 7. PRECAUTIONS:

Do not apply direct to bare metal surfaces. Not suitable for application to surfaces which exceed 120 °C (250°C). Do not use as a self-finish on exterior surfaces.

## 8. FLASH POINTS:

None.