

SUPER G.P ACRYLIC PVA

1. PRODUCT BENEFITS:

- 1.1 Top quality emulsion paint for interior use.
- 1.2 Dries to a superb matt finish with excellent scrub resistance.
- 1.3 White.
- 1.4 Easy application with brush or roller.
- 1.5 Quick drying – excellent recoating properties.
- 1.6 Low odour.

2. USES:

- 2.1 High-grade matt washable wall and ceiling finish for interior use.
- 2.2 Suitable for direct application to new interior plaster, concrete, brickwork and various types of composition boarding.
- 2.3 May be also applied to metal and wooden surfaces provided the surface has been primed with an appropriate primer.
- 2.4 Previously painted oil and enamel surfaces must be suitably rubbed before applying this material.

3. GENERAL DATA:

TYPE	Acrylic CO- PVA	
DRYING TIME AT 25°C	Surface dry: ½-1 hrs	→ Hard dry 3-4 hrs
RECOATING TIME	4 hrs	
VISCOSITY	100 - 110 kreb units	
SPECIFIC GRAVITY	1.42 – 1.44	
SOLIDS BY MASS	36 - 38%	
SOLIDS BY VOLUME	34 – 37%	
SPREADING RATE	Approx. 5m ² /1lt (depending on surface porosity)	
GLOSS	Matt	

4. COLOUR RANGE:

Brilliant White and pastel colours as per Colour Chart.

5. APPLICATION:

- 5.1 Ready for use with brush, roller, or airless spray. For conventional spray, thin with clean water.
- 5.2 Thinner: Not normally thinned but if necessary use water. Thinning will reduce opacity.
- 5.3 Clean up: Water.

6. SURFACE PREPARATION:

All surfaces must be clean and dry before painting. Previously painted surfaces must be in sound condition. Loose flaking paint and efflorescence must be completely removed and any bare metal areas e.g.: nail heads, spot primed with an appropriate primer. Old enamel or oil paint surfaces must be well sanded. Chalked PVA or distemper surfaces must be well brushed and primed with PLASTER PRIMER. For new work or change in colour, apply two coats. Apply one coat for general maintenance.

7. PRECAUTIONS:

Do not apply directly to bare surfaces. Not suitable for application to surfaces which exceed 120°C.

8. FLASH POINTS:

Non flammable.