

BRICK DRESSING

1. PRODUCT BENEFITS:

- 1.1 A clear glossy brick dressing – imparts a tough weather- resistant finish.
- 1.2 Beautifies by restoring deep of colour – highlights the natural shade of stone work.
- 1.3 Strengthens and seals in one operation – prevents defoliation and powdering.
- 1.4 Easy cleaning and maintenance – resist dirt collection.
- 1.5 Quick drying, simple to use – excellent do-it-yourself product.

2. USES:

- 2.1 Specifically for the use on dry face or standard brick, stone and quarry stone surfaces. Imparts a glossy durable finish.
- 2.2 Also suitable for previously varnished brick and stone, provided the surface is sound,
- 2.3 Not recommended as a floor or as a finish for slate, vinyl and ceramic tiles.

3. GENERAL DATA:

TYPE	Phenolic
DRYING TIME AT 25°C	Surface dry: 4-6 hrs → Hard dry 18 hrs
VISCOSITY	30 – 40 sec / F4 / 25 °C
SOLIDS BY MASS	52 - 54%
SOLIDS BY VOLUME	46 – 48%
SPREADING RATE	Approx. 8 m ² /1lt (depending on surface porosity)
GLOSS	High Gloss Clear

4. COLOUR RANGE:

Clear.

5. APPLICATION:

- 5.1 BRUSH : Ready for use. Apply one coat and work the material well into the surface. If a higher gloss is required, apply a second coat after overnight dry.
- 5.2 CONVENTIONAL SPRAY : Thin up to 10% with Mineral Turpentine.
- 5.3 CLEAR UP : Mineral Turpentine.

6. SURFACE PREPARATION:

NEW SURFACES – new brick and stone work must be allowed to weather (dry out) for 1 –2 months. Any loose residue such as builders plaster must be removed. Hose the surface thoroughly and allow to dry for 24 –48 hrs. AGED SURFACES – brush with a stiff broom to remove all dirt and foreign matters. If necessary use MORTAR –CLEAN. Hose and allow the surface to dry for 24 hrs. PREVIOUSLY VARNISHED SURFACES – surface which are cracked or flaking must be completely stripped. Waxed or oiled surfaces must be washed with degreaser, then flushed with water.

7. PRECAUTIONS:

- 7.1 Must not be used on damp surfaces – this could turn the BRICK DRESSING white and lead to loss of adhesion. A simple test for dampness is to hold a fix of PVC sheeting on a rubber mat to the surface with masking tape. After 4 hrs, moisture appears on the underside, the surface is unfit for varnishing.
- 7.2 Do not use on slate, terrazzo or vinyl and ceramic tiles or surfaces which are impervious.
- 7.3 Not suitable on slasto floors.

8. FLASH POINTS:

37 °C