

UNIVERSAL UNDERCOAT

1. PRODUCT BENEFITS:

- 1.1 High quality general purpose undercoat for the use under decorative topcoats for interior or exterior use.
- 1.2 Provides a smooth base with excellent sanding properties.
- 1.3 Excellent adhesion on all properly primed or sealed surfaces.
- 1.4 Good brushing and leveling properties.

2. USES:

An undercoat for air drying protective and decorative paints and may be used on primer steel and timber and on sealed cement, ceiling boards, hard boards and other material used in the building industry.

3. GENERAL DATA:

TYPE	Undercoat based on a medium oil length alkyd.
DRYING TIME AT 25°C	Surface dry: 2-3 hrs
RECOATING TIME	18 hours (overnight)
VISCOSITY	70 kreb units
SPECIFIC GRAVITY	1.5
RECOMMENDED DRY FILM THICKNESS	45 – 55 microns
SPREADING RATE	Approx. 8 m ² /1lt (depending on surface porosity)
GLOSS	Matt

4. COLOUR RANGE:

White only. Colour variations can be made up on request in minium batch quantities.

5. APPLICATION:

- 5.1 Ready for use by brush or roller. Thin for spray application. Apply one coat. Thinning: Mineral Turpentine.

6. SURFACE PREPARATION:

NEW SURFACES - Must be clean and dry primed with an appropriate primer. The hard dry film should be lightly sanded to give a smooth finish. **PREVIOUSLY PAINTED SURFACES** – Must be in sound condition. Loose flaking paint must be removed and bare areas spot primed with an appropriate primer. Build up flaked areas to the same level to the rest of the paintwork and if necessary, apply an overall coat of undercoat.